

NAME

cgs - conjugate gradient squared method with preconditioning

CALLING SEQUENCE

```
[x,err,iter,flag,res] = cgs(A,b,x0,M,maxi,tol)
```

PARAMETERS

A : matrix of size n-by-n or function returning $A*x$
b : right hand side vector
x0 : initial guess vector (default: zeros(n,1))
M : preconditioner: matrix or function returning $M*x$ (In the first case, default: eye(n,n))
maxi : maximum number of iterations (default: n)
tol : error tolerance (default: 1000*%eps)
x : solution vector
err : final residual norm
iter : number of iterations performed
flag : 0 = **cgs** converged to the desired tolerance within **maxi** iterations
 1 = no convergence given **maxi**
res : residual vector

DESCRIPTION

Solves the linear system $Ax=b$ using the Conjugate Gradient Squared method with preconditioning.

EXAMPLE

```
A=makefish(4); b=rand(16,1);x0=zeros(16,1);
[x,err,iter,flag,res] = cgs(A,b,x0)
M=eye(16,16); max_it=16; tol=1000*%eps;
[x,err,iter,flag,res] = cgs(A,b,x0,M,max_it,tol)

deff("y=precond(x)","y=(M+eye(size(M,1),size(M,2)))*x");
deff("y=matvec(x)","y=(A+eye(size(A,1),size(A,1)))*x");

[x,err,iter,flag,res] = cgs(matvec,b,x0,precond,max_it,tol)

[x,err,iter,flag,res] = cgs(A,b,x0,precond)
[x,err,iter,flag,res] = cgs(matvec,b,x0,M)
```

AUTHOR

Adaptation by Aladin Group of the corresponding code of netlib/mltemplatesdev (Univ. of Tennessee and Oak Ridge National Laboratory) - 20 March 2001.

SEE ALSO

bicg, bicgstab, gmres, qmr