

## unknown initiator

### Protocol Purpose

Provide a method to supply a secure channel between a client and server, authenticating the client with a password, and a server with a public key certificate.

### Definition Reference

RFC 2847, <http://www.faqs.org/rfcs/rfc2847.html>

### Model Authors

- Boichut Yohan, LIFC-INRIA Besancon, May 2004
- Sebastian Mödersheim, ETH Zürich, January 2005

### Alice&Bob style

1. A  $\rightarrow$  S:  $S.Na.exp(G,X).H(S.Na.exp(G,X))$
2. S  $\rightarrow$  A:  $S.Na.Nb.exp(G,Y).\{S.Na.Nb.exp(G,Y)\}_{inv(Ks)}$
3. A  $\rightarrow$  S:  $\{login.pwd\}_K$  where  $K = exp(exp(G,Y),X) = exp(exp(G,X),Y)$

### Model Limitations

In real life, the messages 1 and 2 contain respectively the two following items lists.

- target names,
- a fresh random number,
- a list of available confidentiality algorithms,
- a list of available integrity algorithms,
- a list of available key establishment algorithms,
- a context key (or key half) corresponding to the first key estb. alg. given in the previous list,

- GSS context options/choices (such as unilateral or mutual authentication, use of sequencing and replay detection, and so on).

and

- target names,
- the random number sent by the initiator,
- a fresh random number,
- the subset of offered confidentiality algorithms which are supported by the target,
- the subset of offered integrity algorithms which are supported by the target,
- an alternative key establishment algorithm (chosen from the offered list) if the first one offered is unsuitable,
- the key half corresponding to the initiator's key estb. alg. (if necessary), or a context key (or key half) corresponding to the key estb. alg. above,
- GSS context options/choices (such as unilateral or mutual authentication, use of sequencing and replay detection, and so on).

The sets of algorithms agreed are not used by LIPKEY, indeed LIPKEY only uses SPKM for a key establishment. Thus they are not modelled. Furthermore, the key establishment modelled is a la Diffie-Hellman and GSS context options are not modelled.

## **Problems considered: 1**

### **Attacks Found**

None

### **Further Notes**

Here, this unilateral (one-way) authentication version of this protocol. I have a problem to specify authentication since the server does not know A. Then, how to express witness(S,A,...)

## HLPSTL Specification

```
role initiator (
  A,S: agent,
  G: nat,
  H: function,
  Ka,Ks: public_key,
  Login_A_S: message,
  Pwd_A_S:  message,

  SND, RCV: channel (dy))
played_by A def=

local
  State      : nat,
  Na,Nb      : text,
  Rnumber1   : text,
  X          : message,
  Keycompleted : message,
  W          : nat,
  K          : text.text

const sec_i_Log, sec_i_Pwd : protocol_id

init  State := 0

transition

1.  State = 0 /\ RCV(start) =|>
    State' := 1 /\ Na' := new()
                /\ Rnumber1' := new()
                /\ SND(S.Na'.exp(G,Rnumber1').
                      H(S.Na'.exp(G,Rnumber1'))))

2.  State = 1 /\ RCV(S.Na.Nb'.X'.{S.Na.Nb'.X'}_inv(Ks)) =|>
    State' := 2 /\ Keycompleted' := exp(X',Rnumber1)
                /\ SND({Login_A_S.Pwd_A_S}_Keycompleted' )
                /\ secret(Login_A_S,sec_i_Log,{S})
                /\ secret(Pwd_A_S,sec_i_Pwd,{S})
```

```

/\ K' := Login_A_S.Pwd_A_S
/\ witness(A,S,k,Keycompleted')

```

end role

---

```

role target(
    A,S          : agent,
    G            : nat,
    H            : function,
    Ka,Ks        : public_key,
    Login, Pwd   : function,
    SND, RCV     : channel (dy))
played_by S def=

    local State      : nat,
           Na,Nb     : text,
           Rnumber2  : text,
           Y         : message,
           Keycompleted : message,
           W         : nat,
           K         : text.text

    const sec_t_Log, sec_t_Pwd : protocol_id

    init  State := 0

    transition

    1.  State = 0 /\ RCV(S.Na'.Y'.H(S.Na'.Y')) =|>
        State' := 1 /\ Nb' := new()
                /\ Rnumber2' := new()
                /\ SND(S.Na'.Nb'.exp(G,Rnumber2').
                    {S.Na'.Nb'.exp(G,Rnumber2')}_inv(Ks))
                /\ Keycompleted'=exp(Y',Rnumber2')
                /\ secret(Login(A,S),sec_t_Log,{A})
                /\ secret(Pwd(A,S), sec_t_Log,{A})

    21. State = 1 /\ RCV({Login(A,S).Pwd(A,S)}_Keycompleted) =|>
        State' := 2 /\ K' := Login(A,S).Pwd(A,S)

```

/\ request(S,A,k,Keycompleted)

end role

---

```
role session(
    A,S : agent,
    Login, Pwd: function,
    Ka: public_key,
    Ks: public_key,
    H: function,
    G: nat)
def=

    local SndI,RcvI : channel (dy),
        SndT,RcvT : channel (dy)

    composition
        initiator(A,S,G,H,Ka,Ks,Login(A,S),Pwd(A,S),SndI,RcvI) /\
        target(    A,S,G,H,Ka,Ks,Login,Pwd,SndT,RcvT)

end role
```

---

```
role environment()
def=

    const a,s,i,b: agent,
        ka, ki, kb, ks: public_key,
        login, pwd : function,
        h: function,
        g: nat,
        k: protocol_id

    intruder_knowledge = {ki,i, inv(ki),a,b,s,h,g,ks,login(i,s),pwd(i,s),ka
        }

    composition
        session(a,s,login,pwd,ka,ks,h,g)
```

```
 /\ session(b,s,login,pwd,kb,ks,h,g)
 /\ session(i,s,login,pwd,ki,ks,h,g)
```

```
end role
```

---

```
goal
```

```
 %Target authenticates Initiator on k
 authentication_on k
```

```
 %secrecy_of Login, Pwd
 secrecy_of sec_i_Log, sec_i_Pwd,
           sec_t_Log, sec_t_Pwd
```

```
end goal
```

---

```
environment()
```

## References