

EKE: Encrypted Key Exchange

basic

Protocol Purpose

Encrypted key exchange

Definition Reference

<http://citeseer.ist.psu.edu/bellovin92encrypted.html>

Model Authors

- Haykal Tej, Siemens CT IC 3, 2003
- Sebastian Mödersheim, ETH Zürich, December 2003

Alice&Bob style

A -> B : {Ea}_Kab		Key exchange part
B -> A : {{K}_Ea}_Kab		
A -> B : {Ca}_K		
B -> A : {Ca,Cb}_K		Challenge/Response
A -> B : {Cb}_K		Authentication part

Model Limitations

None

Problems considered: 3

Attacks Found

```
i -> (a,3): start
(a,3) -> i: {Ea(1)}_kab
```

```

i -> (a,6): {Ea(1)}_kab
(a,6) -> i: {{K(2)}_Ea(1)}_kab
i -> (a,3): {{K(2)}_Ea(1)}_kab
(a,3) -> i: {Na(3)}_K(2) witness(a,b,na,Na(3))
i -> (a,6): {Na(3)}_K(2)
(a,6) -> i: {Na(3),Nb(4)}_K(2) witness(a,b,nb,Nb(4))
i -> (a,3): {Na(3),Nb(4)}_K(2)
(a,3) -> i: {Nb(4)}_K(2) request(a,b,nb,Nb(4))

```

Parallel session attack, man-in-the-middle between A as initiator and A as responder, attacker masquerades as B, but no secret nonces are exposed.

HLPSL Specification

```

role eke_Init (A,B: agent,
               Kab: symmetric_key,
               Snd,Rcv: channel(dy))
played_by A
def=

  local State    : nat,
        Ea       : public_key,
        Na,Nb,K  : text

  const sec_k1   : protocol_id

  init  State := 0

  transition

  1. State = 0
    /\ Rcv(start)
    =>
    State' := 1

```

```

    /\ Ea' := new()
    /\ Snd({Ea'}_Kab)

2. State = 1
   /\ Rcv({K'}_Ea)_Kab
   =|>
   State' := 2
   /\ Na' := new()
   /\ Snd({Na'}_K')
   /\ secret(K',sec_k1,{A,B})
   /\ witness(A,B,na,Na')

3. State = 2
   /\ Rcv({Na.Nb'}_K)
   =|>
   State' := 3
   /\ Snd({Nb'}_K)
   /\ request(A,B,nb,Nb')

end role

```

```

role eke_Resp (B,A: agent,
               Kab: symmetric_key,
               Snd,Rcv: channel(dy))
played_by B
def=

  local State   : nat,
        Na,Nb,K : text,
        Ea      : public_key

  const sec_k2 : protocol_id

  init  State := 0

  transition

  1. State = 0 /\ Rcv({Ea'}_Kab)
     =|>

```

```

    State' := 1
    /\ K' := new()
    /\ Snd({K'}_Ea')_Kab)
    /\ secret(K',sec_k2,{A,B})

2. State = 1 /\ Rcv({Na'}_K)
   =|>
   State' := 2
   /\ Nb' := new()
   /\ Snd({Na'.Nb'}_K)
   /\ witness(B,A,nb,Nb')

3. State = 2
   /\ Rcv({Nb}_K)
   =|>
   State' := 3
   /\ request(B,A,na,Na)

end role

```

```

role session(A,B: agent,
             Kab: symmetric_key)
def=

    local SA, RA, SB, RB: channel (dy)

    composition
        eke_Init(A,B,Kab,SA,RA)
    /\ eke_Resp(B,A,Kab,SB,RB)

end role

```

```

role environment()
def=

    const a, b    : agent,
           kab     : symmetric_key,

```

```
    na, nb : protocol_id

    intruder_knowledge={a,b}

    composition
      session(a,b,kab)
      /\ session(b,a,kab)

end role
```

```
goal

    secrecy_of sec_k1, sec_k2
    %EKE_Init authenticates EKE_Resp on nb
    authentication_on nb
    %EKE_Resp authenticates EKE_Init on na
    authentication_on na

end goal
```

```
environment()
```

References